


# M SEALS PKV-BLK82

Black Pigmented Virgin PEEK

MATERIAL DATA SHEET (Version 6.0 – 05.2022)



## Description

M Seals PKV-BLK82 material is a high-performance unreinforced virgin PEEK material that has been pigmented black in colour. This material has excellent thermal resistance, high compressive strength, low wear properties and low creep values.

PKV-BLK82 material is commonly used for guide rings, wear rings, bushes, valve seat seals, scraper seals and other applications requiring excellent hydrolysis and steam resistance.

## Physical Properties

Property	Test method	Unit	Typical value
Colour			Black
Density	ASTM D792	g/cm <sup>3</sup>	1.31
Hardness	ASTM D2240	Shore D	82
Tensile strength	ASTM D638	MPa	≥95
Tensile modulus	ASTM D638	MPa	≥3.3
Elongation at break	ASTM D638	%	≥10
Flexural strength	ASTM D790	Mpa	≥140
Compressive strength	ASTM D695	Mpa	≥100
Glass transition temperature *	ASTM D3418	°C	+143
Melting temperature	ASTM D3418	°C	+341
Service temperature short term **		°C	+300
Service temperature long term **		°C	-50/+250

\* (Information found from public sources)

\*\* (Individual testing in application conditions is mandatory)

## Main Characteristics

- Excellent thermal resistance
- High compressive strength
- Good sliding ability
- Good creep resistance
- Good wear properties
- Hydrolysis & steam resistance

## Typical Products

- Wear strip
- Bearing rings / guide rings
- Bushes
- Valve seat seals
- Anti-Extrusion / Back-Up Rings
- Bespoke parts

## Typical Applications

Due to its excellent thermal resistance, compressive strength and sliding ability, this material is an excellent material choice for applications where standard PEEK materials may not be suitable because of colouring. PKV-BLK82 is commonly used within the Oil and Gas and Aerospace industries.

Tel: 0044 (0) 114 243 2777 . Fax: 0044 (0) 114 242 2300 . Mail: [sales.esd@m-seals.co.uk](mailto:sales.esd@m-seals.co.uk) . Web: [www.m-seals.com](http://www.m-seals.com)

M Seals believes that the information above is an accurate description of the typical characteristics and/or uses of the product or products, however M Seals makes no warranty, expressed or implied, that parts manufactured from this / and or any other material will perform satisfactorily in the customers application. It is the customers responsibility to thoroughly test products in their specific application to determine performance, efficiency and safety for each end-use product, device or application. The information and data contained herein are based on standard test pieces according to the corresponding ISO, DIN & ASTM standards and cannot be directly related to finished seals, gaskets or other sealing products and should be used only as a general guide.